

9. Electrical characteristics

		Power supply			Indoor rated	
Type	Model name	Hz	Voltage (V)	MCA (A)	Input power (W)	FLA (A)
Compact cassette	AUYG07LVLA	50	230	0.19	18	0.15
	AUYG09LVLA			0.19	18	0.15
	AUYG12LVLB			0.24	23	0.19
	AUYG14LVLB			0.28	28	0.22
	AUYG18LVLB			0.38	39	0.30
Mini duct	ARYG07LSLAP			0.33	33	0.29
	ARYG09LSLAP			0.38	40	0.33
	ARYG12LSLAP			0.42	47	0.38
	ARYG14LSLAP			0.67	72	0.58
	ARYG18LSLAP			0.61	63	0.49
Slim duct	ARYG07LLTA			0.41	33	0.33
	ARYG09LLTA			0.38	49	0.30
	ARYG12LLTB			0.44	58	0.35
	ARYG14LLTB			0.64	76	0.51
	ARYG18LLTB			0.55	73	0.44
Wall mounted	ASYG07LUCA			0.16	13	0.13
	ASYG09LUCA			0.18	16	0.14
	ASYG12LUCA			0.21	19	0.17
	ASYG14LUCA			0.25	23	0.20
	ASYG07LMCA			0.16	15	0.13
	ASYG07LMCE	0.19	17	0.15		
	ASYG09LMCA					
	ASYG09LMCE					
	ASYG12LMCA	0.24	22	0.19		
	ASYG12LMCE	0.31	28	0.25		
	ASYG14LMCA					
	ASYG14LMCE	0.41	37	0.33		
	ASYG18LFCA					
	ASYG24LFCA					
	ASYG24LFCC	0.66	69	0.53		
Floor/Ceiling	ASYG07KMCC	0.25	23	0.20		
	ASYG09KMCC	0.30	27	0.24		
	ASYG12KMCC	0.30	27	0.24		
	ASYG14KMCC	0.38	33	0.30		
	ABYG14LVTA	0.26	26	0.21		
Floor	ABYG18LVTB	0.45	47	0.36		
	AGYG09LVCA	0.19	16	0.15		
	AGYG12LVCA	0.23	20	0.18		
	AGYG14LVCA	0.25	23	0.20		

MCA: Minimum Circuit Ampacity = Maximum operating current (Full load)

FLA: Full Load Amperes (Fan motor)