





Cooling capacity at rated condition: 14.0 kW (5 HP)

Total rated capacity of indoor unit	Outdoor temperature	Indoor temperature															
		20°CDB/15°CWB		23°CDB/16°CWB		24°CDB/17°CWB		26°CDB/18°CWB		27°CDB/19°CWB		28°CDB/20°CWB		30°CDB/22°CWB		32°CDB/23°CWB	
	°CDB	TC	IP	TC	IP	TC	IP	TC	IP	TC	IP	TC	IP	TC	IP	TC	IP
7.0 (50%)	-5	4.6	0.79	5.2	0.88	5.8	0.96	6.4	1.05	7.0	1.14	7.6	1.22	8.8	1.39	9.4	1.48
	0	4.6	0.79	5.2	0.88	5.8	0.96	6.4	1.05	7.0	1.14	7.6	1.22	8.8	1.39	9.4	1.48
	5	4.6	0.79	5.2	0.88	5.8	0.96	6.4	1.05	7.0	1.14	7.6	1.22	8.8	1.39	9.4	1.48
	10	4.6	0.79	5.2	0.88	5.8	0.96	6.4	1.05	7.0	1.14	7.6	1.22	8.8	1.39	9.4	1.48
	15	4.6	0.79	5.2	0.88	5.8	0.96	6.4	1.05	7.0	1.14	7.6	1.22	8.8	1.39	9.4	1.48
	21	4.6	0.81	5.2	0.90	5.8	0.99	6.4	1.08	7.0	1.17	7.6	1.26	8.8	1.44	9.4	1.52
	23	4.6	0.85	5.2	0.94	5.8	1.03	6.4	1.12	7.0	1.22	7.6	1.31	8.8	1.50	9.4	1.59
	25	4.6	0.88	5.2	0.98	5.8	1.07	6.4	1.17	7.0	1.27	7.6	1.36	8.8	1.56	9.4	1.65
	27	4.6	0.91	5.2	1.01	5.8	1.11	6.4	1.22	7.0	1.32	7.6	1.42	8.8	1.62	9.4	1.73
	30	4.6	0.96	5.2	1.07	5.8	1.18	6.4	1.29	7.0	1.39	7.6	1.50	8.8	1.75	9.4	1.89
	33	4.6	1.02	5.2	1.13	5.8	1.25	6.4	1.36	7.0	1.48	7.6	1.62	8.8	1.91	9.4	2.06
	35	4.6	1.05	5.2	1.17	5.8	1.29	6.4	1.42	7.0	1.57	7.6	1.71	8.8	2.02	9.4	2.18
	37	4.6	1.09	5.2	1.22	5.8	1.36	6.4	1.51	7.0	1.66	7.6	1.81	8.8	2.14	9.4	2.31
	40	4.6	1.16	5.2	1.32	5.8	1.47	6.4	1.63	7.0	1.80	7.6	1.97	8.8	2.32	9.4	2.51
43	4.6	1.26	5.2	1.42	5.8	1.59	6.4	1.77	7.0	1.95	7.6	2.13	8.8	2.53	9.4	2.73	
46	4.6	1.42	5.2	1.61	5.8	1.80	6.4	2.00	7.0	2.21	7.6	2.43	8.8	2.88	9.4	3.11	

MODEL SELECTION

MODEL SELECTION