

Cooling capacity at rated condition: 14.0 kW (5 HP)

Total rated capacity of indoor unit	Outdoor temperature	Indoor temperature															
		20°CDB/15°CWB		23°CDB/16°CWB		24°CDB/17°CWB		26°CDB/18°CWB		27°CDB/19°CWB		28°CDB/20°CWB		30°CDB/22°CWB		32°CDB/23°CWB	
	°CDB	TC	IP	TC	IP	TC	IP	TC	IP	TC	IP	TC	IP	TC	IP	TC	IP
7.0 (50%)	-5	4.6	0.77	5.2	0.85	5.8	0.94	6.4	1.02	7.0	1.10	7.6	1.19	8.8	1.35	9.4	1.44
	0	4.6	0.77	5.2	0.85	5.8	0.94	6.4	1.02	7.0	1.10	7.6	1.19	8.8	1.35	9.4	1.44
	5	4.6	0.77	5.2	0.85	5.8	0.94	6.4	1.02	7.0	1.10	7.6	1.19	8.8	1.35	9.4	1.44
	10	4.6	0.77	5.2	0.85	5.8	0.94	6.4	1.02	7.0	1.10	7.6	1.19	8.8	1.35	9.4	1.44
	15	4.6	0.77	5.2	0.85	5.8	0.94	6.4	1.02	7.0	1.10	7.6	1.19	8.8	1.35	9.4	1.44
	21	4.6	0.79	5.2	0.88	5.8	0.96	6.4	1.05	7.0	1.13	7.6	1.22	8.8	1.39	9.4	1.48
	23	4.6	0.82	5.2	0.91	5.8	1.00	6.4	1.09	7.0	1.18	7.6	1.27	8.8	1.45	9.4	1.54
	25	4.6	0.85	5.2	0.95	5.8	1.04	6.4	1.13	7.0	1.23	7.6	1.32	8.8	1.51	9.4	1.60
	27	4.6	0.89	5.2	0.98	5.8	1.08	6.4	1.18	7.0	1.28	7.6	1.37	8.8	1.57	9.4	1.67
	30	4.6	0.94	5.2	1.04	5.8	1.14	6.4	1.25	7.0	1.35	7.6	1.46	8.8	1.70	9.4	1.83
	33	4.6	0.99	5.2	1.10	5.8	1.21	6.4	1.32	7.0	1.44	7.6	1.57	8.8	1.85	9.4	2.00
	35	4.6	1.02	5.2	1.14	5.8	1.25	6.4	1.38	7.0	1.52	7.6	1.66	8.8	1.96	9.4	2.11
	37	4.6	1.06	5.2	1.18	5.8	1.32	6.4	1.46	7.0	1.61	7.6	1.76	8.8	2.07	9.4	2.23
	40	4.6	1.13	5.2	1.28	5.8	1.43	6.4	1.58	7.0	1.74	7.6	1.91	8.8	2.25	9.4	2.43
	43	4.6	1.23	5.2	1.39	5.8	1.56	6.4	1.73	7.0	1.91	7.6	2.09	8.8	2.48	9.4	2.68
46	4.6	1.39	5.2	1.58	5.8	1.76	6.4	1.96	7.0	2.16	7.6	2.38	8.8	2.82	9.4	3.05	

MODEL SELECTION

MODEL SELECTION