





Cooling capacity at rated condition: 15.5 kW (6 HP)

Total rated capacity of indoor unit	Outdoor temperature	Indoor temperature															
		20°CDB/15°CWB		23°CDB/16°CWB		24°CDB/17°CWB		26°CDB/18°CWB		27°CDB/19°CWB		28°CDB/20°CWB		30°CDB/22°CWB		32°CDB/23°CWB	
	°CDB	TC	IP	TC	IP	TC	IP	TC	IP	TC	IP	TC	IP	TC	IP	TC	IP
7.8 (50%)	-5	5.1	0.94	5.8	1.04	6.4	1.14	7.1	1.24	7.8	1.34	8.4	1.44	9.7	1.64	10.4	1.74
	0	5.1	0.94	5.8	1.04	6.4	1.14	7.1	1.24	7.8	1.34	8.4	1.44	9.7	1.64	10.4	1.74
	5	5.1	0.94	5.8	1.04	6.4	1.14	7.1	1.24	7.8	1.34	8.4	1.44	9.7	1.64	10.4	1.74
	10	5.1	0.94	5.8	1.04	6.4	1.14	7.1	1.24	7.8	1.34	8.4	1.44	9.7	1.64	10.4	1.74
	15	5.1	0.94	5.8	1.04	6.4	1.14	7.1	1.24	7.8	1.34	8.4	1.44	9.7	1.64	10.4	1.74
	21	5.1	0.96	5.8	1.06	6.4	1.17	7.1	1.27	7.8	1.38	8.4	1.48	9.7	1.69	10.4	1.79
	23	5.1	1.00	5.8	1.11	6.4	1.21	7.1	1.32	7.8	1.43	8.4	1.54	9.7	1.76	10.4	1.86
	25	5.1	1.03	5.8	1.15	6.4	1.26	7.1	1.37	7.8	1.49	8.4	1.60	9.7	1.83	10.4	1.94
	27	5.1	1.07	5.8	1.19	6.4	1.31	7.1	1.43	7.8	1.55	8.4	1.66	9.7	1.90	10.4	2.02
	30	5.1	1.13	5.8	1.26	6.4	1.39	7.1	1.51	7.8	1.64	8.4	1.76	9.7	2.05	10.4	2.21
	33	5.1	1.20	5.8	1.33	6.4	1.46	7.1	1.60	7.8	1.74	8.4	1.90	9.7	2.24	10.4	2.41
	35	5.1	1.24	5.8	1.38	6.4	1.52	7.1	1.67	7.8	1.84	8.4	2.01	9.7	2.37	10.4	2.55
	37	5.1	1.28	5.8	1.43	6.4	1.59	7.1	1.76	7.8	1.94	8.4	2.12	9.7	2.50	10.4	2.70
	40	5.1	1.37	5.8	1.54	6.4	1.73	7.1	1.91	7.8	2.11	8.4	2.30	9.7	2.72	10.4	2.93
	43	5.1	1.48	5.8	1.67	6.4	1.87	7.1	2.07	7.8	2.28	8.4	2.50	9.7	2.96	10.4	3.20
46	5.1	1.66	5.8	1.89	6.4	2.11	7.1	2.35	7.8	2.59	8.4	2.85	9.7	3.37	10.4	3.65	

MODEL SELECTION

MODEL SELECTION