
FUITSU AIR CONDITIONING

Product Data Sheet

AJY090LALBH

Nominal Cooling Capacity	(kW)	28.0
Nominal Heating Capacity	(kW)	28.0
Range		V-III
Horse Power		10
Maximum Connectable Indoor Units		21
EER		3.85
COP (Nominal Heating)		4.69
Dimensions (H x W x D)	(mm)	1690 x 930 x 765
Weight	(kg)	252
Airflow Rate (Cooling - Heating) High	(m3/h)	11100 - 11100
Available Static Pressure	(Pa)	Max 82
Sound Pressure Level (Cooling - Heating) High	(dB(A))	58 - 59
Sound Power Level (Cooling - Heating) High	(dB(A))	79 - 81
Refrigerant Type (Global Warming Potential)		R410A (2,088)
Pipe Sizes (Liquid - Gas)		1/2" - 7/8"
Refrigerant Charge (kg)	(kg)	11.7
Refrigerant CO2eq-T		24.4
Unit Power Supply		3Ph-400V-50Hz
Cooling Mode Operating Range	(°C)	-15 to 46
Heating Mode Operating Range	(°C)	-20 to 21



Please visit our webstore for full product and technical documentation



Outdoor Unit Branch Kit (2 Pipe)

Document Downloads

Cooling Capacity **Dimensional Drawing Electrical Characteristics** Heating Capacity Installation Manual Installation Space Noise Curve Product Image Refrigerant Circuit

Spare Parts List All Pages **Specifications** Wiring Diagram

Related Items

UTPCX567A

Units: mm

•Specifications and design are subject to change without notice for further improvement. •Actual products' colors may be different from the colors shown in this printed material.

FUJITSU GENERAL AIR CONDITIONING (UK) LIMITED Unit 150, Centennial Park, Centennial Avenue, Elstree, Borehamwood, Herts, WD6 3SG www.fujitsu-general.com/uk sales@fgac.fujitsu-general.com Tel: +44 (0) 208 731 3450 Fax: +44 (0) 208 731 3451