

AJY090LALDH

Please visit our webstore for full product and technical documentation



| Nominal Cooling Capacity | (kW) | 28.0 |
|---|---------|------------------|
| Nominal Heating Capacity | (kW) | 28.0 |
| Range | | V-III |
| Horse Power | | 10 |
| Maximum Connectable Indoor Units | | 21 |
| EER | | 3.09 |
| COP (Nominal Heating) | | 4.31 |
| Dimensions (H x W x D) | (mm) | 1690 x 930 x 765 |
| Weight | (kg) | 252 |
| Airflow Rate (Cooling - Heating) High | (m3/h) | 11100 - 11100 |
| Available Static Pressure | (Pa) | Max 82 |
| Sound Pressure Level (Cooling - Heating) High | (dB(A)) | 58 - 60 |
| Sound Power Level (Cooling - Heating) High | (dB(A)) | 79 - 81 |
| Refrigerant Type (Global Warming Potential) | | R410A (2,088) |
| Pipe Sizes (Liquid - Gas) | | 1/2" - 7/8" |
| Refrigerant Charge (kg) | (kg) | 11.7 |
| Refrigerant CO2eq-T | | 24.4 |
| Unit Power Supply | | 3Ph-400V-50Hz |
| Cooling Mode Operating Range | (°C) | -15 to 46 |
| Heating Mode Operating Range | (°C) | -20 to 21 |
| | | |




Document Downloads


Cooling Capacity Dimensional Drawing Electrical Characteristics Heating Capacity Installation Manual Installation Space Noise Curve **Product Image** Refrigerant Circuit


Spare Parts List All Pages Specifications Wiring Diagram


Related Items

UTPCX567A Outdoor Unit Branch Kit (2 Pipe)









Units: mm

[•]Specifications and design are subject to change without notice for further improvement. • Actual products' colors may be different from the colors shown in this printed material.