

Model name			ARXC60GATH	ARXC072GTEH	ARXC090GTEH	ARXC096GTEH	
Power supply			230 V ~ 50 Hz				
Available voltage range			198—264 V				
Capacity	Cooling	kW	18.0	22.4	25.0	28.0	
		Btu/h	61,400	76,400	85,300	95,500	
	Heating	kW	20.0	25.0	28.0	31.5	
		Btu/h	68,200	85,300	95,500	107,500	
Input power		W	730	681	819	838	
Static pressure range		Pa	100 to 250	0 to 300			
Standard static pressure		Pa	100	150			
Fan	Airflow rate	HIGH	m ³ /h (l/s)	3,500 (972)	3,900 (1,083)	4,300 (1,195)	4,850 (1,347)
		MED		3,000 (833)	3,300 (917)	4,000 (1,111)	4,250 (1,181)
		LOW		2,460 (683)	3,000 (833)	3,500 (972)	3,600 (1,000)
	Type × Q'ty	Sirocco × 2					
Motor output		W	540	700 × 2			
Sound pressure level*		HIGH	dB (A)	49	47	48	48
		MED		45	43	46	45
		LOW		42	40	44	42
Heat exchanger type	Dimensions (H × W × D)		mm	336 × 890 × 53.2	378 × 1,250 × 53.2		508 × 1,250 × 76.2
	Length			890	1,250		
	Fin pitch				1.45		1.60
	Rows × Stages			4 × 16	4 × 18		4 × 20
	Face area		m ²	0.30	0.50		0.64
	Pipe type (Material)		Grooved H-pin (Copper)				
	Fin	Type (Material)	Slit (Aluminum)				Louver (Aluminum)
		Surface treatment	Hydrophilic coating				
Air filter	Model name		UTD-LF60KA	—			
	Net material		PP honeycomb				
Enclosure	Material		Galvanized sheet iron				
	Color		—				
Dimensions (H × W × D)	Net	mm	400 × 1,050 × 500	450 × 1,587 × 700		550 × 1,587 × 700	
	Gross		460 × 1,230 × 640	520 × 1,750 × 825		620 × 1,750 × 825	
Weight	Net	kg	46	84		105	
	Gross		51	100		125	
Connection pipe diameter	Liquid (Flare)		Ø 9.52 (Ø 3/8)				
	Gas (Flare)		Ø 19.05 (Ø 3/4)		Ø 22.22 (Ø 7/8)		
	Drain hose		VP25 I.D.: Ø 25 (1); O.D.: Ø 32 (1-1/4)				
NOTES:							
<ul style="list-style-type: none"> Specifications are based on the following conditions: <ul style="list-style-type: none"> Cooling: Indoor temperature of 27 °CDB/19 °CWB, and outdoor temperature of 35 °CDB/24 °CWB. Heating: Indoor temperature of 20 °CDB/15 °CWB, and outdoor temperature of 7 °CDB/6 °CWB. Pipe length: 7.5 m, Height difference: 0 m. (Between outdoor unit and indoor unit.) Protective function might work when using it outside the operation range. *: Sound pressure level: <ul style="list-style-type: none"> Measured values in manufacturer's anechoic chamber. Because of the surrounding sound environment, the sound levels measured in actual installation conditions might be higher than the specified values here. 							

INDOOR
UNITS

INDOOR
UNITS