

Model name			ARXD014GLEH	ARXD018GLEH	ARXD024GLEH	
Power supply			230 V ~ 50 Hz			
Available voltage range			198—264 V			
Capacity	Cooling	kW	4.5	5.6	7.1	
		Btu/h	15,400	19,100	24,200	
	Heating	kW	5.0	6.3	8.0	
		Btu/h	17,100	21,500	27,300	
Input power		W	92	83	122	
Static pressure range		Pa	0 to 90		0 to 50	
Standard static pressure		Pa	25			
Fan	Airflow rate	HIGH	800 (222)	940 (261)	1,330 (369)	
		MED—HIGH	680 (189)	820 (228)	1,140 (317)	
		MED	600 (167)	730 (203)	1,020 (283)	
		MED—LOW	520 (144)	630 (175)	900 (250)	
		LOW	440 (122)	540 (150)	780 (217)	
		QUIET	340 (94)	470 (131)	610 (169)	
	Type × Q'ty		Sirocco × 2	Sirocco × 3	Sirocco × 4	
Motor output		W	81	96	96	
Sound pressure level*		HIGH	34		35	
		MED—HIGH	32	31		
		MED	30		29	
		MED—LOW	28		27	
		LOW	25	25	24	
		QUIET	22	23	21	
Heat exchanger type	Dimensions (H × W × D)		mm	294 × 500 × 39.9	294 × 700 × 39.9	294 × 900 × 39.9
	Length			500	700	900
	Fin pitch			1.3		
	Rows × Stages			3 × 14		
	Face area		m ²	0.15	0.21	0.26
	Pipe type (Material)			Grooved H-pin (Copper)		
	Fin	Type		Slit (Aluminum)		
		Surface treatment		Hydrophilic coating		
Air filter	Net material			PP honeycomb		
Enclosure	Material			Galvanized sheet iron		
	Color			—		
Dimensions (H × W × D)	Net		mm	198 × 700 × 620	198 × 900 × 620	198 × 1,100 × 620
	Gross			270 × 935 × 770	270 × 1,135 × 770	270 × 1,335 × 770
Weight	Net		kg	18	22	26
	Gross			23	27	31
Connection pipe diameter	Liquid (Flare)		mm (in)	Ø 6.35 (Ø 1/4)		Ø 9.52 (Ø 3/8)
	Gas (Flare)			Ø 12.70 (Ø 1/2)		Ø 15.88 (Ø 5/8)
	Drain hose			VP25 I.D.: Ø 25 (1); O.D.: Ø 32 (1-1/4)		
NOTES:						
<ul style="list-style-type: none"> Specifications are based on the following conditions: <ul style="list-style-type: none"> Cooling: Indoor temperature of 27 °CDB/19 °CWB, and outdoor temperature of 35 °CDB/24 °CWB. Heating: Indoor temperature of 20 °CDB/15 °CWB, and outdoor temperature of 7 °CDB/6 °CWB. Pipe length: 7.5 m, Height difference: 0 m. (Between outdoor unit and indoor unit.) Protective function might work when using it outside the operation range. *: Sound pressure level: <ul style="list-style-type: none"> Measured values in manufacturer's anechoic chamber. Because of the surrounding sound environment, the sound levels measured in actual installation conditions might be higher than the specified values here. 						