

1. Specifications

Type			Duct					
			Inverter heat pump					
Model name			ARXG09KLLAP	ARXG12KLLAP	ARXG14KLLAP	ARXG18KLLAP		
Power supply			230 V ~ 50 Hz					
Power supply intake			Outdoor unit					
Available voltage range			198—264 V					
Capacity	Cooling	Rated	kW	2.5	3.5	4.3	5.2	
			Btu/h	8,500	11,900	14,700	17,700	
		Min.—Max.	kW	0.90—2.70	0.90—3.70	0.90—4.50	0.90—5.40	
			Btu/h	3,100—9,200	3,100—12,600	3,100—15,300	3,100—18,400	
	Heating	Rated	kW	3.2	4.1	5.0	6.0	
			Btu/h	10,900	14,000	17,000	20,500	
Min.—Max.		kW	0.90—3.90	0.90—4.40	0.90—5.30	0.90—6.30		
		Btu/h	3,100—13,300	3,100—15,000	3,100—18,000	3,100—21,400		
Input power	Cooling	Rated	kW	0.69	1.09	1.37	1.66	
				Max.	1.59	1.78	2.12	2.33
	Heating	Rated		0.88	1.17	1.42	1.71	
				Max.	1.59	1.78	2.12	2.33
Current	Cooling	Rated	A	3.4	5.2	6.4	7.6	
	Heating			4.4	5.8	6.6	7.9	
Power factor	Cooling	%		88.2	91.1	93.1	95.0	
	Heating			87.0	87.7	93.5	94.1	
EER	Cooling		kW/kW	3.62	3.21	3.14	3.13	
COP	Heating			3.64	3.50	3.52	3.51	
Moisture removal			L/h (pints/h)	0.7 (1.2)	1.3 (2.3)	1.5 (2.6)	2.0 (3.5)	
Maximum operating current *1			Cooling	A	6.9	7.7	9.2	10.1
			Heating		6.9	7.7	9.2	10.1
Fan	Airflow rate	Cooling	m ³ /h	HIGH	600	650	800	940
				MED	550	600	700	880
				LOW	500	550	600	820
				QUIET	450	480	750	
		Heating		HIGH	600	650	800	940
				MED	550	600	700	880
				LOW	500	550	600	820
				QUIET	450	480	750	
	Type × Q'ty			Sirocco fan × 2				
	Motor output			W	81			
Recommended static pressure range			Pa	0 to 90				
Sound pressure level *2	Cooling	HIGH	dB (A)	28	29	32		
				MED	27	28	30	
				LOW	26		28	29
				QUIET	25		26	27
	Heating	HIGH		28	29	32		
				MED	26	28	30	
				LOW	25		26	29
				QUIET	24		25	27
Heat exchanger type	Dimensions (H × W × D)		mm	294 × 500 × 39.9			294 × 700 × 39.9	
	Fin pitch			1.3				
	Rows × Stages			3 × 14				
	Pipe type			Copper tube				
	Fin type			Aluminum				
Enclosure	Material			Steel sheet				
	Color			—				
Dimensions (H × W × D)	Net		mm	198 × 700 × 620			198 × 900 × 620	
	Gross			276 × 968 × 772			276 × 1,168 × 772	
Weight	Net		kg	17			20	
	Gross			22			26	
Connection pipe	Size	Liquid	mm (in)	Ø 6.35 (Ø 1/4)				
		Gas		Ø 9.52 (Ø 3/8)		Ø 12.70 (Ø 1/2)		
Drain hose	Method			Flare				
	Material			PVC				
Operation range	Size		mm	Ø 25 (I.D.), Ø 32 (O.D.)				
	Cooling	°C		18 to 32				
		%RH		80 or less				
Heating	°C		16 to 30					
Remote control (Option)			Wired remote controller, Wireless remote controller, Mobile app*3 (FGLair™)					

NOTES:

- Specifications are based on the following conditions:
 - Cooling: Indoor temperature of 27 °CDB/19 °CWB, and outdoor temperature of 35 °CDB/24 °CWB.
 - Heating: Indoor temperature of 20 °CDB/15 °CWB, and outdoor temperature of 7 °CDB/6 °CWB.
 - Standard static pressure: 25 Pa
 - Pipe length: 5.0 m, Height difference: 0 m. (Between outdoor unit and indoor unit.)
- Protective function might work when using it outside the operation range.
- *1: Maximum operating current is the total current of the indoor unit and the outdoor unit.
- *2: Sound pressure level:
 - Measured values in manufacturer's anechoic chamber.
 - Because of the surrounding sound environment, the sound levels measured in actual installation conditions might be higher than the specified values here.
- *3: Available on Google Play™ store or on App Store®. Optional WLAN adapter is also required. For details, refer to the setting manual.

Specifications for ErP Lot10							
Model name		ARXG09KLLAP	ARXG12KLLAP	ARXG14KLLAP	ARXG18KLLAP		
Energy efficiency class	Cooling	A ⁺					
	Heating (Average)	A					
Pdesign	Cooling	kW	2.5 (35°C)	3.5 (35°C)	4.3 (35°C)	5.2 (35°C)	
	Heating (Average)		2.3 (-10°C)	2.8 (-10°C)	3.2 (-10°C)	3.8 (-10°C)	
SEER	Cooling	kWh/kWh	5.90	5.80	5.60	5.80	
SCOP	Heating (Average)		3.80				
Annual energy consumption	QCE	kWh/a	148	211	269	313	
	QHE (Average)		847	1,031	1,177	1,398	
Sound power level	Cooling	HIGH	dB (A)	57	58	60	58
	Heating			57	58	60	58