

2-2. Mini duct type

| Model name | | | | ARXG07KSLAP | ARXG09KSLAP | ARXG12KSLAP | ARXG14KSLAP | |
|-----------------------------|------------------------|---------|------------|--------------------------|-------------|-------------|-------------|-----|
| Power supply | | | | 1Ø 230 V ~50 Hz | | | | |
| Available voltage range | | | | 198—264 V | | | | |
| Capacity | | | kW class | 2.0 | 2.5 | 3.5 | 4.0 | |
| Input power | Fan | HIGH | W | 33 | 40 | 47 | 72 | |
| | | MED | | 23 | 23 | 26 | 44 | |
| | | LOW | | 20 | 20 | 22 | 30 | |
| | | QUIET | | 18 | 18 | 18 | 18 | |
| Running current | | | A | 0.29 | 0.33 | 0.38 | 0.58 | |
| Fan | Airflow rate | Cooling | HIGH | m ³ /h | 550 | 600 | 650 | 800 |
| | | | MED | | 440 | 450 | 490 | 640 |
| | | | LOW | | 390 | 400 | 430 | 530 |
| | | | QUIET | | 360 | 360 | 360 | 360 |
| | | Heating | HIGH | | 550 | 600 | 650 | 800 |
| | | | MED | | 440 | 450 | 490 | 640 |
| | | | LOW | | 390 | 400 | 430 | 530 |
| | | | QUIET | | 360 | 360 | 360 | 360 |
| | Type × Q'ty | | | Sirocco fan × 2 | | | | |
| | Motor output | | | W | 75 | | | |
| Recommended static pressure | | | Pa | 0 to 30 | | | 0 to 50 | |
| Sound pressure level * | Cooling | HIGH | dB (A) | 29 | 29 | 31 | 35 | |
| | | MED | | 26 | 26 | 27 | 30 | |
| | | LOW | | 24 | 24 | 25 | 27 | |
| | | QUIET | | 23 | 23 | 23 | 23 | |
| | Heating | HIGH | | 29 | 29 | 31 | 35 | |
| | | MED | | 26 | 26 | 27 | 30 | |
| | | LOW | | 24 | 24 | 25 | 27 | |
| | | QUIET | | 23 | 23 | 23 | 23 | |
| Sound power level | Cooling | dB (A) | 52 | 54 | 55 | 60 | | |
| | Heating | | 53 | 56 | 57 | 62 | | |
| Heat exchanger type | Dimensions (H × W × D) | | mm | 336 × 490 × 26.6 | | | | |
| | Fin pitch | | mm | 1.3 | | | | |
| | Rows × Stages | | | 2 × 16 | | | | |
| | Pipe type | | | Copper tube | | | | |
| | Fin type | | | Aluminum | | | | |
| Enclosure | Material | | | Steel sheet | | | | |
| | Color | | | — | | | | |
| Dimensions (H × W × D) | Net | | mm | 198 × 700 × 450 | | | | |
| | Gross | | | 250 × 930 × 580 | | | | |
| Weight | Net | | kg | 15.5 | | | | |
| | Gross | | | 19.0 | | | | |
| Connection pipe | Size | Liquid | mm (in) | Ø6.35 (Ø1/4) | | | | |
| | | Gas | | Ø9.52 (Ø3/8) | | | | |
| | Method | | | | Flare | | | |
| Operation range | Cooling | °C | 18 to 32 | | | | | |
| | | %RH | 80 or less | | | | | |
| | Heating | °C | 16 to 30 | | | | | |
| Drain hose | Material | | | Hard PVC | | | | |
| | Size | | mm | Ø 25 (I.D.), Ø 32 (O.D.) | | | | |

NOTES:

- Values mentioned in the table are based on the following conditions:
 - Static pressure: 10 Pa
- The protective function might work when using it outside the operation range.
- *: Sound pressure level:
 - These are the measured values in the manufacturer's anechoic chamber.
 - Because of the surrounding sound environment, the sound levels measured in actual installation conditions might be higher than the specified values here.