

2-3. Slim duct type

Model name				ARYG07LLTA	ARYG09LLTA	ARYG12LLTB		
Power supply				1Ø 230 V ~50 Hz				
Available voltage range				198—264 V				
Capacity		kW class		2.0	2.5	3.5		
Input power		W		33	49	58		
Running current				A	0.33	0.30	0.35	
Fan	Airflow rate	Cooling	HIGH	m ³ /h	550	600	650	
			MED		490	550	600	
			LOW		470	500	550	
			QUIET		440	450	480	
		Heating	HIGH		550	600	650	
			MED		490	550	600	
			LOW		470	500	550	
			QUIET		440	450	480	
	Type × Q'ty		Sirocco fan × 2					
	Motor output		W		80	81		
Recommended static pressure				Pa				
				0 to 90				
Sound pressure level *	Cooling	HIGH	dB (A)	28	28	29		
		MED		26	27	28		
		LOW		25	26	27		
		QUIET		24	25	26		
	Heating	HIGH		28	28	29		
		MED		26	26	28		
		LOW		25	25	27		
		QUIET		24	24	24		
Sound power level		Cooling		dB (A)		57	58	
		Heating				57	58	
Heat exchanger type		Dimensions (H × W × D)		mm		294 × 500 × 26.6	294 × 500 × 39.9	
		Fin pitch		mm		1.3		
		Rows × Stages				2 × 14	3 × 14	
		Pipe type		Copper tube				
		Fin type		Aluminum				
Enclosure		Material		Steel sheet				
		Color		—				
Dimensions (H × W × D)		Net		mm				
		Gross		198 × 700 × 620				
Weight		Net		kg				
		Gross		274 × 945 × 772				
Connection pipe		Size		mm (in)				
		Method		Flare				
Operation range		Cooling		°C				
		Heating		%RH				
				°C				
Drain hose		Material		Hard PVC				
		Size		mm				
Remote controller type				Wired (Wireless [option])				

NOTES:

- Values mentioned in the table are based on the following conditions:
 - Static pressure: 25 Pa
- The protective function might work when using it outside the operation range.
- *: Sound pressure level:
 - These are the measured values in the manufacturer's anechoic chamber.
 - Because of the surrounding sound environment, the sound levels measured in actual installation conditions might be higher than the specified values here.