

## **ARYG24LMLA**

## Please visit our webstore for full product and technical documentation




Unit Type		Medium Static Ducted
Remote Controller		Included
Nominal Cooling Capacity	(kW)	6.8
Nominal Heating Capacity	(kW)	8.0
Height	(mm)	270
Width	(mm)	1135
Depth	(mm)	700
Weight	(kg)	38
Filter		UTDLF25NA / UTDRF204
Standard Static Pressure	(Pa)	35
Static Pressure Ranget	(Pa)	30 to 150
Airflow Rate - Cooling - High	(m3/h)	1100
Airflow Rate - Heating - High	(m3/h)	1100
Sound Pressure Level - Cooling - High	(dB(A))	31
Sound Pressure Level - Cooling - Low	(dB(A))	25
Sound Pressure Level - Heating - High	(dB(A))	31
Sound Pressure Level - Heating - Low	(dB(A))	25
Sound Power Level - Cooling - High	(dB(A))	60
Sound Power Level - Heating - High	(dB(A))	62
Moisture Removal	(l/h)	2.5
Refrigerant Type (Global Warming Potential)		R410A (2,088)
Liquid Pipe Size		1/4"
Gas Pipe Size		5/8"
Unit Power Supply		From Outdoor Unit


## **Document Downloads**


<u>Airflow - Fan Curve</u> Controls & Accessories <u>Dimensional Drawing</u> **Function Settings** Inputs & Outputs **Installation Manual** Noise Curve Operation Manual **Product Image** 


Spare Parts List All Pages **Specifications** Wiring Diagram

Unit: mm









<sup>•</sup>Specifications and design are subject to change without notice for further improvement.

<sup>•</sup> Actual products' colors may be different from the colors shown in this printed material.