## Product Data Sheet

**FUJITSU** | AIR CONDITIONING

# ARYG36LMLE

### Please visit our webstore for full product and technical documentation




**Specifications** Wiring Diagram


Document Downloads Airflow - Fan Curve


Controls & Accessories **Dimensional Drawing** Function Settings Inputs & Outputs Installation Manual Noise Curve Product Image Spare Parts List All Pages

Unit Type		Medium Static Ducted
Remote Controller		Included
Nominal Cooling Capacity	(kW)	9.4
Nominal Heating Capacity	(kW)	11.2
Height	(mm)	270
Width	(mm)	1135
Depth	(mm)	700
Weight	(kg)	40
Filter	-	UTDLF25NA / UTDRF204
Standard Static Pressure	(Pa)	47
Static Pressure Ranget	(Pa)	30 to 150
Airflow Rate - Cooling - High	(m3/h)	1900
Airflow Rate - Heating - High	(m3/h)	2100
Sound Pressure Level - Cooling - High	(dB(A))	39
Sound Pressure Level - Cooling - Low	(dB(A))	26
Sound Pressure Level - Heating - High	(dB(A))	42
Sound Pressure Level - Heating - Low	(dB(A))	26
Sound Power Level - Cooling - High	(dB(A))	65
Sound Power Level - Heating - High	(dB(A))	69
Moisture Removal	(l/h)	3
Refrigerant Type (Global Warming Potential)		R410A (2,088)
Liquid Pipe Size		3/8"
Gas Pipe Size		5/8"
Unit Power Supply		From Outdoor Unit

### Unit: mm









#### •Specifications and design are subject to change without notice for further improvement. •Actual products' colors may be different from the colors shown in this printed material.

FUJITSU GENERAL AIR CONDITIONING (UK) LIMITED Unit 150, Centennial Park, Centennial Avenue, Elstree, Borehamwood, Herts, WD6 3SG www.fujitsu-general.com/uk sales@fgac.fujitsu-general.com Tel: +44 (0) 208 731 3450 Fax: +44 (0) 208 731 3451