

2. Specifications

2-1. Compact cassette type

Model name				AUXB004GLEH	AUXB007GLEH	AUXB009GLEH	
Power supply				230 V ~ 50 Hz			
Available voltage range				198—264 V			
Capacity	Cooling	kW		1.1	2.2	2.8	
		Btu/h		3,800	7,500	9,600	
	Heating	kW		1.3	2.8	3.2	
		Btu/h		4,400	9,600	10,900	
Input power				W	25		
Fan	Airflow rate	HIGH	m ³ /h (l/s)	530/530*1 (147/147)	540 (150)	550 (153)	
		MED—HIGH		490/480*1 (136/133)	500 (139)	520 (144)	
		MED		450/430*1 (125/119)	460 (128)	480 (133)	
		MED—LOW		420/380*1 (117/106)	420 (117)	440 (122)	
		LOW		390/340*1 (108/94)	390 (108)	400 (111)	
		QUIET		350/300*1 (97/83)	350 (97)		
	Type × Q'ty	Turbo × 1					
Motor output				W	54		
Sound pressure level*2		HIGH	dB (A)	34/34*1	34	35	
		MED—HIGH		32/31*1	32	33	
		MED		30/29*1	30	31	
		MED—LOW		28/26*1	28	29	
		LOW		27/24*1	27		
		QUIET		25/21*1	25		
Heat exchanger type	Dimensions (H × W × D)		mm	210 × 1,310 × 13.3			
	Length			210 × 1,250 × 13.3			
	Fin pitch			1,280			
	Rows × Stages			1.2			
	Face area		m ²	2 × 10			
	Pipe type (Material)			0.27			
	Fin		Type (Material)	Grooved H-pin (Copper)			
			Surface treatment	Slit (Aluminum)			
Air filter	Net material			Hydrophilic coating			
Enclosure	Material			PP honeycomb			
	Color			Galvanized sheet iron			
Dimensions (H × W × D)	Net		mm	—			
	Main body			245 × 570 × 570			
	Gross			265 × 730 × 625			
Weight	Net		kg	14.5	15		
	Gross			18			
Connection pipe diameter	Liquid (Flare)		mm (in)	Ø 6.35 (Ø 1/4)			
	Gas (Flare)			Ø 9.52 (Ø 3/8)			
	Drain hose			VP25 I.D.: Ø 25 (1); O.D.: Ø 32 (1-1/4)			
Cassette grille (Grid type: Option)	Model name			UTG-UF*E-W			
	Color			White Approximate color of Munsell 9PB 9.1/0.2			
	Dimensions (H × W × D)	Net		mm	50 × 620 × 620		
		Gross			120 × 765 × 755		
	Weight	Net		kg	2.3		
		Gross			4.5		
Cassette grille (Standard type: Option)	Model name			UTG-UF*C-W			
	Color			White Approximate color of Munsell N9.25/			
	Dimensions (H × W × D)	Net		mm	50 × 700 × 700		
		Gross			120 × 765 × 755		
	Weight	Net		kg	2.6		
		Gross			4.5		
NOTES:							
<ul style="list-style-type: none"> Specifications are based on the following conditions: <ul style="list-style-type: none"> Cooling: Indoor temperature of 27 °CDB/19 °CWB, and outdoor temperature of 35 °CDB/24 °CWB. Heating: Indoor temperature of 20 °CDB/15 °CWB, and outdoor temperature of 7 °CDB/6 °CWB. Pipe length: 7.5 m, Height difference: 0 m. (Between outdoor unit and indoor unit.) Protective function might work when using it outside the operation range. *1: This value is "Cooling operation/Heating operation". *2: Sound pressure level: <ul style="list-style-type: none"> Measured values in manufacturer's anechoic chamber. Because of the surrounding sound environment, the sound levels measured in actual installation conditions might be higher than the specified values here. 							