

Model name				AUXB012GLEH	AUXB014GLEH	AUXB018GLEH	AUXB024GLEH		
Power supply				230 V ~ 50 Hz					
Available voltage range				198—264 V					
Capacity	Cooling	kW		3.6	4.5	5.6	7.1		
		Btu/h		12,300	15,400	19,100	24,200		
	Heating	kW		4.1	5.0	6.3	8.0		
		Btu/h		14,000	17,100	21,500	27,300		
Input power				W					
Fan	Airflow rate	HIGH	m ³ /h (l/s)	600 (167)	680 (189)	710 (197)	1,030 (286)		
		MED—HIGH		560 (156)	620 (172)	660 (183)	910 (253)		
		MED		520 (144)	560 (156)	590 (164)	790 (219)		
		MED—LOW		480 (133)	500 (139)	520 (144)	680 (189)		
		LOW		430 (119)	440 (122)	460 (128)	560 (156)		
		QUIET		390 (108)		400 (111)	450 (125)		
	Type × Q'ty	Turbo × 1							
Motor output				W					
Sound pressure level*		HIGH	dB (A)	37	38	41	50		
		MED—HIGH		34	37	39	46		
		MED		33	34	36	43		
		MED—LOW		31	32	33	39		
		LOW		29	30		35		
		QUIET		27		30			
Heat exchanger type	Dimensions (H × W × D)		mm	210 × 1,310 × 13.3		210 × 1,360 × 13.3			
				210 × 1,250 × 13.3		210 × 1,295 × 13.3			
	Length			1,280		1,295			
	Fin pitch			1.2		1.3			
	Rows × Stages			2 × 10		3 × 10			
	Face area			m ²	0.27		0.28		
	Pipe type (Material)			Grooved H-pin (Copper)					
	Fin			Type	Slit (Aluminum)				
		Surface treatment	Hydrophilic coating						
Air filter	Net material			PP honeycomb					
Enclosure	Material			Galvanized sheet iron					
	Color			—					
Dimensions (H × W × D)	Net		mm	245 × 570 × 570					
	Gross			265 × 730 × 625					
Weight	Net		kg	15		17			
	Gross			19		20			
Connection pipe diameter	Liquid (Flare)		mm (in)	Ø 6.35 (Ø 1/4)		Ø 9.52 (Ø 3/8)			
	Gas (Flare)			Ø 12.70 (Ø 1/2)					
	Drain hose			VP25					
				I.D.: Ø 25 (1); O.D.: Ø 32 (1-1/4)					
Cassette grille (Grid type: Option)	Model name			UTG-UF*E-W					
	Color			White					
				Approximate color of Munsell 9PB 9.1/0.2					
	Dimensions (H × W × D)	Net		mm	50 × 620 × 620				
		Gross			120 × 765 × 755				
	Weight	Net		kg	2.3				
Gross		4.5							
Cassette grille (Standard type: Option)	Model name			UTG-UF*C-W					
	Color			White					
				Approximate color of Munsell N9.25/					
	Dimensions (H × W × D)	Net		mm	50 × 700 × 700				
		Gross			120 × 765 × 755				
	Weight	Net		kg	2.6				
Gross		4.5							
NOTES:									
<ul style="list-style-type: none"> Specifications are based on the following conditions: <ul style="list-style-type: none"> Cooling: Indoor temperature of 27 °CDB/19 °CWB, and outdoor temperature of 35 °CDB/24 °CWB. Heating: Indoor temperature of 20 °CDB/15 °CWB, and outdoor temperature of 7 °CDB/6 °CWB. Pipe length: 7.5 m, Height difference: 0 m. (Between outdoor unit and indoor unit.) Protective function might work when using it outside the operation range. *: Sound pressure level: <ul style="list-style-type: none"> Measured values in manufacturer's anechoic chamber. Because of the surrounding sound environment, the sound levels measured in actual installation conditions might be higher than the specified values here. 									