

2-2. 4-way flow cassette type

Model name				AUXD18GALH	AUXD24GALH
Power supply				230 V ~ 50 Hz	
Available voltage range				198—264 V	
Capacity	Cooling	kW		5.6	7.1
		Btu/h		19,100	24,200
	Heating	kW		6.3	8.0
		Btu/h		21,500	27,300
Input power				W	
Fan	Airflow rate	HIGH	m ³ /h (l/s)	1,150 (319)	1,280 (356)
		MED		940 (261)	1,040 (289)
		LOW		870 (242)	
	Type × Q'ty	Turbo × 1			
Motor output				W	
Sound pressure level*	HIGH	MED	LOW	dB (A)	
				36	38
				30	33
					29
Heat exchanger type	Dimensions (H × W × D)		mm	210 × 2,087 × 13.3	
	Length			210 × 2,021 × 13.3	
	Fin pitch		2,054		
	Rows × Stages		1.2		
	Face area		2 × 10		
	Pipe type (Material)		m ²		
	Type		0.42		
	Surface treatment		Grooved H-pin (Copper)		
Air filter	Type		Anti-mold		
	Net material		PP honeycomb		
Enclosure	Material		Galvanized sheet iron		
	Color		—		
Dimensions (H × W × D)	Net	Main body	mm	246 × 840 × 840	
	Gross			318 × 960 × 980	
Weight	Net	kg	22		
	Gross		27		
Connection pipe diameter	Liquid (Flare)	mm (in)	Ø 9.52 (Ø 3/8)		
	Gas (Flare)		Ø 15.88 (Ø 5/8)		
	Drain hose		VP25		
	I.D.: Ø 25 (1); O.D.: Ø 32 (1-1/4)				
Cassette grille (Option)	Model name		UTG-UG*A-W		
	Color		White		
	Dimensions (H × W × D)		mm	Approximate color of Munsell N9.25/	
	Net	50 × 950 × 950			
	Gross	115 × 1,020 × 1,000			
	Weight	Net	kg	5.5	
Gross		8.5			
NOTES:					
<ul style="list-style-type: none"> Specifications are based on the following conditions: <ul style="list-style-type: none"> Cooling: Indoor temperature of 27 °CDB/19 °CWB, and outdoor temperature of 35 °CDB/24 °CWB. Heating: Indoor temperature of 20 °CDB/15 °CWB, and outdoor temperature of 7 °CDB/6 °CWB. Pipe length: 7.5 m, Height difference: 0 m. (Between outdoor unit and indoor unit.) Protective function might work when using it outside the operation range. *: Sound pressure level: <ul style="list-style-type: none"> Measured values in manufacturer's anechoic chamber. Because of the surrounding sound environment, the sound levels measured in actual installation conditions might be higher than the specified values here. 					