

8-2. 4-way flow cassette type

Model	Mode	Airflow		
		m ³ /h	l/s	CFM
AUXD18GALH	HIGH	1,150	319	677
	MED	940	261	553
	LOW	870	242	512
AUXD24GALH	HIGH	1,280	356	753
	MED	1,040	289	612
	LOW	870	242	512
AUXA18GALH	HIGH	1,420	394	836
	MED	1,230	342	724
	LOW*1	1,100/1,000	306/278	647/589
AUXA24GALH	HIGH	1,420	394	836
	MED	1,230	342	724
	LOW*1	1,100/1,000	306/278	647/589
AUXA30GALH	HIGH	1,600	444	942
	MED	1,300	361	765
	LOW	1,100	306	647
AUXA34GALH	HIGH	1,750	486	1,030
	MED	1,300	361	765
	LOW	1,100	306	647
AUXA36GALH	HIGH	1,800	500	1,059
	MED	1,300	361	765
	LOW	1,100	306	647
AUXA45GALH	HIGH	1,900	528	1,059
	MED	1,370	381	765
	LOW	1,100	306	647
AUXA54GALH	HIGH	2,000	556	1,118
	MED	1,370	381	806
	LOW	1,100	306	647

*1: This value is "Cooling operation/Heating operation".