

Model name				AUXK018GLEH	AUXK024GLEH	AUXK030GLEH	AUXK034GLEH	
Power supply				230 V ~ 50 Hz				
Available voltage range				198—264 V				
Capacity	Cooling	kW		5.6	7.1	9.0	10.0	
		Btu/h		19,100	24,200	30,700	34,100	
	Heating	kW		6.3	8.0	10.0	11.2	
		Btu/h		21,500	27,300	34,100	38,200	
Input power				W		40	47	
Fan	Airflow rate	HIGH	m ³ /h (l/s)	1,420 (394)		1,440 (400)		
		MED—HIGH		1,360 (378)		1,400 (389)		
		MED		1,300 (361)		1,340 (372)		
		MED—LOW		1,270 (353)		1,300 (361)		
		LOW		1,200 (333)		1,280 (356)		
	QUIET	1,150 (319)		1,150 (319)				
Type × Q'ty		Turbo × 1						
Motor output				W				81
Sound pressure level*		HIGH	dB (A)	38		39		
		MED—HIGH		37		38		
		MED		36		37		
		MED—LOW		35		36		
		LOW		34		35		
	QUIET	33						
Heat exchanger type	Dimensions (H × W × D)		mm	252 × 2,127 × 13.3		252 × 2,124 × 13.3		
				252 × 2,061 × 13.3		252 × 2,062 × 13.3		
	Length			2,094		2,062		
	Fin pitch			1.2		1.3		
	Rows × Stages			2 × 12		3 × 12		
	Pipe type (Material)		Grooved H-pin (Copper)					
Air filter	Net material		PP honeycomb					
	Material		Galvanized sheet iron					
Enclosure	Color		—					
	Material		Galvanized sheet iron					
Dimensions (H × W × D)	Net		mm	288 × 840 × 840				
	Gross			340 × 960 × 950				
Weight	Net		kg	26.5		29.5		
	Gross			31.5		34.0		
Connection pipe diameter	Liquid (Flare)		mm (in)	Ø 6.35 (Ø 1/4)		Ø 9.52 (Ø 3/8)		
	Gas (Flare)			Ø 12.70 (Ø 1/2)		Ø 15.88 (Ø 5/8)		
	Drain hose			VP25 I.D.: Ø 25 (1); O.D.: Ø 32 (1-1/4)				
Cassette grille (Option)	Material		PS					
	Color		UTG-UK*C-W: White Approximate color of Munsell N9.25/ UTG-UK*A-B: Black Approximate color of Munsell N2/					
	Dimensions (H × W × D)	Net		mm	53 × 950 × 950			
		Gross			110 × 1,000 × 1,010			
	Weight	Net		kg	6.0			
		Gross			10			

NOTES:

- Specifications are based on the following conditions:
 - Cooling: Indoor temperature of 27 °CDB/19 °CWB, and outdoor temperature of 35 °CDB/24 °CWB.
 - Heating: Indoor temperature of 20 °CDB/15 °CWB, and outdoor temperature of 7 °CDB/6 °CWB.
 - Pipe length: 7.5 m, Height difference: 0 m. (Between outdoor unit and indoor unit.)
- Protective function might work when using it outside the operation range.
- *: Sound pressure level:
 - Measured values in manufacturer's anechoic chamber.
 - Because of the surrounding sound environment, the sound levels measured in actual installation conditions might be higher than the specified values here.

INDOOR
UNITS

INDOOR
UNITS