

| Model name | | | | AUXK018GLEH | AUXK024GLEH | AUXK030GLEH | AUXK034GLEH | | |
|--------------------------|------------------------|---|-------------------------|------------------------------------|-------------|--------------------|-------------|----|--|
| Power supply | | | | 230 V ~ 50 Hz | | | | | |
| Available voltage range | | | | 198—264 V | | | | | |
| Capacity | Cooling | kW | | 5.6 | 7.1 | 9.0 | 10.0 | | |
| | | Btu/h | | 19,100 | 24,200 | 30,700 | 34,100 | | |
| | Heating | kW | | 6.3 | 8.0 | 10.0 | 11.2 | | |
| | | Btu/h | | 21,500 | 27,300 | 34,100 | 38,200 | | |
| Input power | | | | W | | 40 | 47 | | |
| Fan | Airflow rate | HIGH | m ³ /h (l/s) | 1,420 (394) | | 1,440 (400) | | | |
| | | MED—HIGH | | 1,360 (378) | | 1,400 (389) | | | |
| | | MED | | 1,300 (361) | | 1,340 (372) | | | |
| | | MED—LOW | | 1,270 (353) | | 1,300 (361) | | | |
| | | LOW | | 1,200 (333) | | 1,280 (356) | | | |
| | QUIET | 1,150 (319) | | 1,150 (319) | | | | | |
| Type × Q'ty | | Turbo × 1 | | | | | | | |
| Motor output | | | | W | | | | 81 | |
| Sound pressure level* | | HIGH | dB (A) | 38 | | 39 | | | |
| | | MED—HIGH | | 37 | | 38 | | | |
| | | MED | | 36 | | 37 | | | |
| | | MED—LOW | | 35 | | 36 | | | |
| | | LOW | | 34 | | 35 | | | |
| | QUIET | 33 | | | | | | | |
| Heat exchanger type | Dimensions (H × W × D) | | mm | 252 × 2,127 × 13.3 | | 252 × 2,124 × 13.3 | | | |
| | | | | 252 × 2,061 × 13.3 | | 252 × 2,062 × 13.3 | | | |
| | Length | | | 2,094 | | 2,062 | | | |
| | Fin pitch | | | 1.2 | | 1.3 | | | |
| | Rows × Stages | | | 2 × 12 | | 3 × 12 | | | |
| | Pipe type (Material) | | Grooved H-pin (Copper) | | | | | | |
| | Fin | Type | Slit (Aluminum) | | | | | | |
| Surface treatment | | Hydrophilic coating | | | | | | | |
| Air filter | Net material | | PP honeycomb | | | | | | |
| Enclosure | Material | | Galvanized sheet iron | | | | | | |
| | Color | | — | | | | | | |
| Dimensions (H × W × D) | Net | Main body | mm | 288 × 840 × 840 | | | | | |
| | Gross | | | 340 × 960 × 950 | | | | | |
| Weight | Net | | kg | 26.5 | | 29.5 | | | |
| | Gross | | | 31.5 | | 34.0 | | | |
| Connection pipe diameter | Liquid (Flare) | | mm (in) | Ø 6.35 (Ø 1/4) | | Ø 9.52 (Ø 3/8) | | | |
| | Gas (Flare) | | | Ø 12.70 (Ø 1/2) | | Ø 15.88 (Ø 5/8) | | | |
| | Drain hose | | | VP25 | | | | | |
| | | | | I.D.: Ø 25 (1); O.D.: Ø 32 (1-1/4) | | | | | |
| Cassette grille (Option) | Material | | PS | | | | | | |
| | Color | UTG-UK*C-W: White Approximate color of Munsell N9.25/ | | | | | | | |
| | | UTG-UK*A-B: Black Approximate color of Munsell N2/ | | | | | | | |
| | Dimensions (H × W × D) | Net | mm | 53 × 950 × 950 | | | | | |
| | | Gross | | 110 × 1,000 × 1,010 | | | | | |
| | Weight | Net | kg | 6.0 | | | | | |
| Gross | | 10 | | | | | | | |

NOTES:

- Specifications are based on the following conditions:
 - Cooling: Indoor temperature of 27 °CDB/19 °CWB, and outdoor temperature of 35 °CDB/24 °CWB.
 - Heating: Indoor temperature of 20 °CDB/15 °CWB, and outdoor temperature of 7 °CDB/6 °CWB.
 - Pipe length: 7.5 m, Height difference: 0 m. (Between outdoor unit and indoor unit.)
- Protective function might work when using it outside the operation range.
- *: Sound pressure level:
 - Measured values in manufacturer's anechoic chamber.
 - Because of the surrounding sound environment, the sound levels measured in actual installation conditions might be higher than the specified values here.

INDOOR
UNITS

INDOOR
UNITS