

Model name				AUXK018GLEH	AUXK024GLEH	AUXK030GLEH	AUXK034GLEH	
Power supply				230 V ~ 50 Hz				
Available voltage range				198—264 V				
Capacity	Cooling	kW		5.6	7.1	9.0	10.0	
		Btu/h		19,100	24,200	30,700	34,100	
	Heating	kW		6.3	8.0	10.0	11.2	
		Btu/h		21,500	27,300	34,100	38,200	
Input power				W		40	47	
Fan	Airflow rate	HIGH MED—HIGH MED MED—LOW LOW QUIET	m <sup>3</sup> /h (l/s)	1,420 (394)		1,440 (400)		
				1,360 (378)		1,400 (389)		
				1,300 (361)		1,340 (372)		
				1,270 (353)		1,300 (361)		
				1,200 (333)		1,280 (356)		
				1,150 (319)		1,150 (319)		
	Type × Q'ty	Turbo × 1						
Motor output				W				
Sound pressure level*	HIGH MED—HIGH MED MED—LOW LOW QUIET	dB (A)	38		39			
			37		38			
			36		37			
			35		36			
			34		35			
			33		33			
Heat exchanger type	Dimensions (H × W × D)		mm	252 × 2,127 × 13.3		252 × 2,124 × 13.3		
	252 × 2,061 × 13.3			252 × 2,062 × 13.3		252 × 1,999 × 13.3		
	Length		2,094		2,062			
	Fin pitch		1.2		1.3			
	Rows × Stages		2 × 12		3 × 12			
	Pipe type (Material)		Grooved H-pin (Copper)					
	Fin	Type	Slit (Aluminum)					
Surface treatment		Hydrophilic coating						
Air filter	Net material		PP honeycomb					
Enclosure	Material		Galvanized sheet iron					
	Color		—					
Dimensions (H × W × D)	Net	Main body	mm	288 × 840 × 840				
	Gross			340 × 960 × 950				
Weight	Net	kg	26.5		29.5			
	Gross		31.5		34.0			
Connection pipe diameter	Liquid (Flare)	mm (in)	Ø 6.35 (Ø 1/4)		Ø 9.52 (Ø 3/8)			
	Gas (Flare)		Ø 12.70 (Ø 1/2)		Ø 15.88 (Ø 5/8)			
	Drain hose		VP25					
			I.D.: Ø 25 (1); O.D.: Ø 32 (1-1/4)					
Cassette grille (Option)	Material		PS					
	Color	UTG-UK*C-W: White Approximate color of Munsell N9.25/						
		UTG-UK*A-B: Black Approximate color of Munsell N2/						
	Dimensions (H × W × D)	Net	mm	53 × 950 × 950				
		Gross		110 × 1,000 × 1,010				
	Weight	Net	kg	6.0				
		Gross		10				

**NOTES:**

- Specifications are based on the following conditions:
  - Cooling: Indoor temperature of 27 °CDB/19 °CWB, and outdoor temperature of 35 °CDB/24 °CWB.
  - Heating: Indoor temperature of 20 °CDB/15 °CWB, and outdoor temperature of 7 °CDB/6 °CWB.
  - Pipe length: 7.5 m, Height difference: 0 m. (Between outdoor unit and indoor unit.)
- Protective function might work when using it outside the operation range.
- \*: Sound pressure level:
  - Measured values in manufacturer's anechoic chamber.
  - Because of the surrounding sound environment, the sound levels measured in actual installation conditions might be higher than the specified values here.

INDOOR  
UNITS

INDOOR  
UNITS