

2-5. One way flow cassette type

Model name				AUXV004GLEH	AUXV007GLEH	AUXV009GLEH	AUXV012GLEH	
Power supply				230 V ~ 50 Hz				
Available voltage range				198—264 V				
Capacity	Cooling	kW		1.1	2.2	2.8	3.6	
		Btu/h		3,800	7,500	9,600	12,300	
	Heating	kW		1.3	2.8	3.2	4.0	
		Btu/h		4,400	9,600	10,900	13,600	
Input power				W		30	42	
Fan	Airflow rate	HIGH		460 (128)	550 (153)	670 (186)		
		MED—HIGH		440 (122)	440 (122)	520 (144)		
		MED		420 (117)	420 (117)	480 (133)		
		MED—LOW		400 (111)	400 (111)	450 (125)		
		LOW		380 (106)	380 (106)	410 (114)		
		QUIET		360 (100)	360 (100)	360 (100)		
	Type × Q'ty	Motor output		W		Sirocco × 2		
Sound pressure level*	HIGH		38	42	45			
	MED—HIGH		37	37	41			
	MED		36	36	39			
	MED—LOW		35	35	38			
	LOW		33	33	36			
	QUIET		32	32	32			
Heat exchanger type	Dimensions (H × W × D)		mm	336 × 490 × 13.3		336 × 490 × 26.6		
	Length			490				
	Fin pitch			1.3				
	Rows × Stages		1 × 16		2 × 16			
	Pipe type (Material)		Grooved H-pin (Copper)					
	Fin		Type		Slit (Aluminum)			
			Surface treatment		Hydrophilic coating			
Air filter	Net material		PP honeycomb					
Enclosure	Material		Galvanized sheet iron					
	Color		—					
Dimensions (H × W × D)	Net		mm	198 × 785 × 570				
	Gross			305 × 1,135 × 695				
Weight	Net		kg	18	19			
	Gross			26	27			
Connection pipe diameter	Liquid (Flare)		mm (in)	Ø 6.35 (Ø 1/4)		Ø 6.35 (Ø 1/4)		
	Gas (Flare)			Ø 9.52 (Ø 3/8)		Ø 12.70 (Ø 1/2)		
	Drain hose			VP25 I.D.: Ø 25 (1); O.D.: Ø 32 (1-1/4)				
Cassette grille (Option)	Model name		UTG-UN*A-W					
	Color		White Approximate color of Munsell N9.25/					
	Dimensions (H × W × D)	Net		mm	43 × 950 × 620			
		Gross			150 × 1,090 × 735			
	Weight	Net		kg	6.5			
Gross		11						
NOTES:								
<ul style="list-style-type: none"> Specifications are based on the following conditions: <ul style="list-style-type: none"> Cooling: Indoor temperature of 27 °CDB/19 °CWB, and outdoor temperature of 35 °CDB/24 °CWB. Heating: Indoor temperature of 20 °CDB/15 °CWB, and outdoor temperature of 7 °CDB/6 °CWB. Pipe length: 7.5 m, Height difference: 0 m. (Between outdoor unit and indoor unit.) Protective function might work when using it outside the operation range. *: Sound pressure level: <ul style="list-style-type: none"> Measured values in manufacturer's anechoic chamber. Because of the surrounding sound environment, the sound levels measured in actual installation conditions might be higher than the specified values here. 								