

Model name				AUXV014GLEH	AUXV018GLEH	AUXV024GLEH
Power supply				230 V ~ 50 Hz		
Available voltage range				198—264 V		
Capacity	Cooling	kW		4.5	5.6	7.1
		Btu/h		15,400	19,100	24,200
	Heating	kW		5.0	6.3	8.0
		Btu/h		17,100	21,500	27,300
Input power				W		
Fan	Airflow rate	HIGH	m ³ /h (l/s)	720 (200)	890 (247)	1,150 (319)
		MED—HIGH		660 (183)	840 (233)	1,020 (283)
		MED		630 (175)	770 (214)	940 (261)
		MED—LOW		600 (167)	710 (197)	790 (219)
		LOW		580 (161)	660 (183)	700 (194)
	QUIET	550 (153)		580 (161)	610 (169)	
Type × Q'ty		Sirocco × 4				
Motor output			W			
Sound pressure level*		HIGH	dB (A)	37	44	49
		MED—HIGH		36	43	47
		MED		35	40	45
		MED—LOW		34	38	42
		LOW		33	36	39
		QUIET		32	34	36
Heat exchanger type	Dimensions (H × W × D)		mm	336 × 890 × 26.6		336 × 890 × 26.6
	Length			890		
	Fin pitch			1.3		1.3, 1.45
	Rows × Stages		2 × 16			
	Pipe type (Material)		Grooved H-pin (Copper)			
	Fin	Type	Slit (Aluminum)			
		Surface treatment	Hydrophilic coating			
Air filter	Net material		PP honeycomb			
Enclosure	Material		Galvanized sheet iron			
	Color		—			
Dimensions (H × W × D)	Net	Main body	mm	198 × 1,190 × 570		
	Gross			305 × 1,530 × 695		
Weight	Net		kg	26	27	
	Gross			36		
Connection pipe diameter	Liquid (Flare)		mm (in)	Ø 6.35 (Ø 1/4)		Ø 9.52 (Ø 3/8)
	Gas (Flare)			Ø 12.70 (Ø 1/2)		Ø 15.88 (Ø 5/8)
	Drain hose			VP25 I.D.: Ø 25 (1); O.D.: Ø 32 (1-1/4)		
Cassette grille (Option)	Model name		UTG-UN*B-W			
	Color		White Approximate color of Munsell N9.25/			
	Dimensions (H × W × D)	Net	mm	43 × 1,360 × 620		
		Gross		150 × 1,495 × 735		
	Weight	Net	kg	8.5		
Gross		14				
NOTES:						
<ul style="list-style-type: none"> • Specifications are based on the following conditions: <ul style="list-style-type: none"> – Cooling: Indoor temperature of 27 °CDB/19 °CWB, and outdoor temperature of 35 °CDB/24 °CWB. – Heating: Indoor temperature of 20 °CDB/15 °CWB, and outdoor temperature of 7 °CDB/6 °CWB. – Pipe length: 7.5 m, Height difference: 0 m. (Between outdoor unit and indoor unit.) • Protective function might work when using it outside the operation range. • *: Sound pressure level: <ul style="list-style-type: none"> – Measured values in manufacturer's anechoic chamber. – Because of the surrounding sound environment, the sound levels measured in actual installation conditions might be higher than the specified values here. 						