

9. Electrical characteristics

Type	Model name	Power supply			Indoor rated	
		Hz	Voltage (V)	MCA (A)	Input power (W)	FLA (A)
Compact cassette	AUYG07LVLA	50	230	0.19	18	0.15
	AUYG09LVLA			0.19	18	0.15
	AUYG12LVLB			0.24	23	0.19
	AUYG14LVLB			0.28	28	0.22
	AUYG18LVLB			0.38	39	0.30
Mini duct	ARYG07LSLAP			0.33	33	0.29
	ARYG09LSLAP			0.38	40	0.33
	ARYG12LSLAP			0.42	47	0.38
	ARYG14LSLAP			0.67	72	0.58
	ARYG18LSLAP			0.61	63	0.49
Slim duct	ARYG07LLTA			0.41	33	0.33
	ARYG09LLTA			0.38	49	0.30
	ARYG12LLTB			0.44	58	0.35
	ARYG14LLTB			0.64	76	0.51
	ARYG18LLTB			0.55	73	0.44
Wall mounted	ASYG07LUCA			0.16	13	0.13
	ASYG09LUCA			0.18	16	0.14
	ASYG12LUCA			0.21	19	0.17
	ASYG14LUCA			0.25	23	0.20
	ASYG07LMCA			0.16	15	0.13
	ASYG07LMCE	0.19	17	0.15		
	ASYG09LMCA					
	ASYG09LMCE					
	ASYG12LMCA	0.24	22	0.19		
	ASYG12LMCE	0.31	28	0.25		
	ASYG14LMCA					
	ASYG14LMCE					
	ASYG18LFCA	0.41	37	0.33		
	ASYG24LFCA	0.66	69	0.53		
	ASYG24LFCC					
ASYG07KMCC	0.25	23	0.20			
ASYG09KMCC	0.30	27	0.24			
ASYG12KMCC	0.30	27	0.24			
ASYG14KMCC	0.38	33	0.30			
Floor/Ceiling	ABYG14LVTA	0.26	26	0.21		
	ABYG18LVTB	0.45	47	0.36		
Floor	AGYG09LVCA	0.19	16	0.15		
	AGYG12LVCA	0.23	20	0.18		
	AGYG14LVCA	0.25	23	0.20		

MCA: Minimum Circuit Ampacity = Maximum operating current (Full load)

FLA: Full Load Amperes (Fan motor)