




















# 11. Accessories

## 11-1. Models: AUYG18LVLB and AUYG24LVLA

Part name	Exterior	Q'ty	Part name	Exterior	Q'ty
Operating manual		1	Hose band		1
Installation manual		1	Drain hose insulation		1
Coupler heat insulation (Large)		1	Remote controller		1
Coupler heat insulation (Small)		1	Battery		2
Special nut A (Large flange)		4	Remote controller holder		1
Special nut B (Small flange)		4	Tapping screw		2
Template (Carton top)		1	Cable tie		2
Drain hose		1	Wire clammer		1


## 12. Optional parts

### 12-1. Controllers





Exterior	Part name	Model name	Summary
	Wired remote controller	UTY-RVNYM	Large and full-dot liquid crystal screen, wide and large keys easy to press, user-intuitive arrow key. Wire type: Polar 3-wire
	Wired remote controller	UTY-RNNYM	Room temperature can be controlled by detecting the temperature accurately with built-in thermo sensor. Wire type: Polar 3-wire
	Simple remote controller	UTY-RSNYM	Compact remote controller concentrates on the basic functions such as Start/Stop, fan control, temperature setting, and operation mode. Wire type: Polar 3-wire

**NOTE:** Available functions may differ by the remote controller. For details, refer to the operation manual.

## 12-2. Cassette grille

Exterior	Part name	Model name	Summary
	Cassette grille	UTG-UFYD-W	The form of grille discharges wind away from the ceiling making it difficult to leave dirt marks.

## 12-3. Others

Exterior	Part name	Model name	Summary
	External connect kit	UTY-XWZX	Use to connect with various peripheral devices and air conditioner PCB.
	Air outlet shutter plate	UTR-YDZB	Installed at the air outlet when 3-directions mode is performed.
	Fresh-air intake kit	UTZ-VXAA	By attaching Fresh-air intake kit to the indoor unit, it can be taken in fresh air of up to 10% of "high" air volume of the indoor unit.
	Insulation for high humidity	UTZ-KXGC	Install when the under-roof condition is expected to be the humidity of over 80% and the temperature of over 30 °C.